

 This work is protected by  
US copyright laws and is for  
instructors' use only.


**Solutions Manual**  
*to accompany*

# **Water and Wastewater Technology Seventh Edition**

**Mark J. Hammer**  
**Mark J. Hammer Jr.**



Upper Saddle River, New Jersey  
Columbus, Ohio



---

**Copyright © 2012 by Pearson Education, Inc., Upper Saddle River, New Jersey 07458.**

Pearson Prentice Hall. All rights reserved. Printed in the United States of America. This publication is protected by Copyright and permission should be obtained from the publisher prior to any prohibited reproduction, storage in a retrieval system, or transmission in any form or by any means, electronic, mechanical, photocopying, recording, or likewise. For information regarding permission(s), write to: Rights and Permissions Department.

**Pearson Prentice Hall™** is a trademark of Pearson Education, Inc.

**Pearson®** is a registered trademark of Pearson plc

**Prentice Hall®** is a registered trademark of Pearson Education, Inc.

Instructors of classes using Hammer and Hammer, *Water and Wastewater Technology, 7e*, may reproduce material from the instructor's manual for classroom use.




10 9 8 7 6 5 4 3 2 1

ISBN-13: 978-0-13-511405-6

ISBN-10: 0-13-511405-5

# Water and Wastewater Technology



This solutions manual has been prepared by the authors for classroom use by instructors teaching from *Water and Wastewater Technology, Seventh Edition*. Textbook problems are an effective method of measuring student's understanding and performance; therefore, the safekeeping of solutions is important to all instructors. Under no circumstance should any solution in this manual be reproduced and distributed or otherwise released in any form for student use. Obviously, solutions must be presented in a classroom by writing calculations on the classroom board or by projecting calculations using a projector. Your cooperation in maintaining the integrity of the homework solutions is appreciated.

The inside book cover is intended as a reference and as a teaching aid to the overall treatment processes.

Mark J. Hammer  
Mark J. Hammer Jr.

## 2-1 CHEMISTRY

2-1

- (a)  $\text{Al}_2(\text{SO}_4)_3 \cdot 14.3 \text{H}_2\text{O} = 2\text{Al} + 3\text{S} + 12\text{O} + 14.3(2\text{H} + \text{O})$   
 $\text{MW} = 2 \cdot 27.0 + 3 \cdot 32.1 + 12 \cdot 16.0 + 14.3(2 \cdot 1.0 + 16.0) = 600$   
 $\text{EW} = 600/6 = 100$
- (b)  $\text{lime} = \text{CaO}$   
 $\text{MW} = 40.1 + 16.0 = 56.1$   
 $\text{EW} = 56.1/2 = 28.0$
- (c)  $\text{FeSO}_4 \cdot 7\text{H}_2\text{O} = \text{Fe} + \text{S} + 11\text{O} + 14\text{H}$   
 $\text{MW} = 55.8 + 32.1 + 11 \cdot 16.0 + 14 \cdot 1.0 = 278$   
 $\text{EW} = 278/2 = 139$
- (d)  $\text{floussilicic acid} = \text{H}_2\text{SiF}_6 = 2\text{H} + \text{Si} + 6\text{F}$   
 $\text{MW} = 2 \cdot 1.0 + 28.1 + 6 \cdot 19.0 = 144$   
 $\text{EW}$  is not applicable since  $\text{F}^-$  is released in solution.
- (e)  $\text{soda ash} = \text{Na}_2\text{CO}_3 = 2\text{Na} + \text{C} + 3\text{O}$   
 $\text{MW} = 2 \cdot 23.0 + 12.0 + 3 \cdot 16.0 = 106$   
 $\text{EW} = 106/2 = 53$

2-2.

- (a)  $\text{NaNO}_3 = \text{Na}^+ + \text{NO}_3^-$   
 (b)  $\text{H}_2\text{SO}_4 = 2\text{H}^+ + \text{SO}_4^{2-}$   
 (c)  $\text{Ca}(\text{OCl})_2 = \text{Ca}^{++} + 2\text{OCl}^-$   
 (d)  $\text{Na}_2\text{CO}_3 = 2\text{Na}^+ + \text{CO}_3^{2-}$  (below pH 8.3,  $\text{HCO}_3^-$ , Equation 2-7)

2-3.  $\text{F concentration} = 1.0 \frac{(6 \cdot 19.0)}{144} = 0.79 \text{ mg/l}$

2-4.  $\text{Hardness} = 29.0 \frac{50}{20} + 16.4 \frac{50}{12.2} = 140 \text{ mg/l}$

2-5.  $\text{Ca}^{++} = 20 \frac{175}{50} = 70 \text{ mg/l}$

$\text{Mg}^{++} = 12.2 \frac{40}{50} = 9.8 \text{ mg/l}$

2-6.  $\text{Alkalinity} = 12 \frac{50}{30.0} + 100 \frac{50}{61.0} = 102 \text{ mg/l}$

2-7.  $\text{Alkalinity} = 20 \frac{50}{30} + 34 \frac{50}{61} = 61.2 \text{ mg/l}$

2-8.  $\text{Calcium} = 94/20.0 = 4.70 \text{ meq/l}$   
 $\text{Magnesium} = 24/12.2 = 1.97$   
 $\text{Sodium} = 14/23.0 = 0.61$   
 $\text{Bicarbonate} = 317/61.0 = 5.20$   
 $\text{Sulfate} = 67/48.0 = 1.40$   
 $\text{Chloride} = 24/35.5 = 0.68$

0	4.7	6.67	7.28
Ca		Mg	Na
HCO <sub>3</sub>		SO <sub>4</sub>	Cl
0	5.2	6.60	7.28

2-9.

Component	mg/l	EW	meq/l
Ca	60	20.0	3.0
Mg	10	12.2	0.8
Na	7	23.0	0.3
K	20	39.1	0.5
HCO <sub>3</sub> (Alk)	115	50.0	2.3
SO <sub>4</sub>	96	48.0	2.0
Cl	11	35.5	0.3

0	3.0	3.8	4.1	4.6
Ca		Mg	Na	K
HCO <sub>3</sub>		SO <sub>4</sub>	Cl	
0	2.3	4.3		4.6

2-10.

Calcium =  $108/20.0 = 5.40$  meq/l  
 Magnesium =  $44/12.2 = 3.61$   
 Sodium =  $138/23.0 = 6.00$   
 Bicarbonate =  $146/61.0 = 2.39$   
 Sulfate =  $110/48.0 = 2.29$   
 Chloride =  $366/35.5 = 10.31$

0	5.4	9.0	15.0
Ca		Mg	Na
HCO <sub>3</sub>	SO <sub>4</sub>	Cl	
0	2.4	4.7	15.0

Carbonate hardness =  $2.4 \cdot 50 = 120$  mg/l  
 Noncarbonate hardness =  $(5.4 - 2.4)50 = 150$  mg/l  
 Total hardness =  $9.0 \cdot 50 = 450$  mg/l  
 Alkalinity =  $2.4 \cdot 50 = 120$  mg/l

2-11.

Component	Mg/l	EW	meq/l
Ca hardness	150	50.0	3.0
Mg hardness	65	50.0	1.3
Na	8	23.0	0.3
K	4	39.1	0.1
Alkalinity	190	50.0	3.8
SO <sub>4</sub>	29	48.0	0.6
Cl	10	35.5	0.3

0		3.0		4.3	4.6	4.7
Ca		Mg		Na	K	
HCO <sub>3</sub>			SO <sub>4</sub>	Cl		
0		3.8		4.4	4.7	

Hypothetical combinations: 3.0 Ca(HCO<sub>3</sub>)<sub>2</sub>; 0.8 Mg(HCO<sub>3</sub>)<sub>2</sub>; 0.5 MgSO<sub>4</sub>;  
0.1 Na<sub>2</sub>SO<sub>4</sub>; 0.2 NaCl; 0.1 KCl

2-12.  $\text{H}_2\text{SO}_4 + 2\text{CaCO}_3 = \text{Ca}(\text{HCO}_3)_2 + \text{CaSO}_4$   
 $\frac{X}{98.1} = \frac{20 \text{ mg/l}}{2 \times 100} \quad X = 9.8 \text{ mg/l of H}_2\text{SO}_4$


2-13.  $\frac{\text{Wt. of acid / l}}{\text{MW} \cdot 1000} = \frac{10 \text{ mg / l}}{98,100 \text{ mg / mole}} = 0.000,101,9 \text{ mole / l H}^+$

$$\text{pH} = \log \left[ \frac{1}{0.000,101,9} \right] = 4.0$$


2-14. (a)  $\frac{\text{Wt. of acid/l}}{\text{MW} \cdot 1000} = \frac{3.0 \text{ mg/l}}{98,100 \text{ mg/mole}} = 0.000,030,6 \text{ mole/l H}^+$

$$\text{pH} = \log \left[ \frac{1}{0.000,030,6} \right] = 4.5$$

(b)  $\frac{1.0}{98,100} = 0.000,010,2 \text{ mole/l H}^+, \text{ pH} = 5.0$



$$\frac{X}{44.0} = \frac{35}{74.1} = \frac{Y}{100} \quad X = 20.8 \text{ mg/l, } Y = 47.2 \text{ mg/l}$$




$$\frac{47.2}{100} = \frac{X}{44.0}$$

$$X = 20.8 \text{ mg/l}$$




Since one equivalent of lime (CaO) reacts with one equivalent of calcium hardness, the calculation for this problem is easily performed using equivalent weights.

$$\frac{\text{CaO}}{\text{CaCO}_3} = \frac{28.0}{50} = \frac{X}{100} \quad X = 56 \text{ mg/l}$$



$$\frac{3\text{Mn}}{2\text{KMnO}_4} = \frac{3 \cdot 54.9}{2 \cdot 158} = \frac{X}{1.0} \quad X = 0.52 \text{ mg/l as Mn}$$



$$\frac{A}{56.1} = \frac{B}{88.0} = \frac{45 \text{ mg/l}}{40.1} \quad A = 63 \text{ mg/l CaO} \quad B = 99 \text{ mg/CO}_2$$

- 2-20. (a) The rate of a zero-order reaction depends only on time since it is independent of the concentration of any reactant or product.  
 (b) The rate of a first-order reaction proceeds at a rate directly proportional to the remaining concentration of one reactant.

- 2-21. The value of  $\theta$  in Equation 2-26 is 1.072 if the rate of a reaction doubles for a 10°C temperature increase, therefore, the increase from a 5°C increase is:

$$k_2/k_1 = (1.072)^5 = 1.42$$

- 2-22 Using Table 2-5,  
 DO saturation at 15°C at sea level = 10.1 mg/l  
 At an elevation of 2000 ft, DO saturation = 9.5, more accurately 9.3 mg/l

- 2-23 DO saturation at 22°C at sea level = 8.7 mg/l  
 At an elevation of 4000 ft, 7.5